

PRIMA 10



NEW for 2016

New design, bigger 10kg working bowl, 2-piece enrober.

PRIMA delivers the benefits of FBM's continuous tempering technology to demanding confectioners and chocolatiers who need an enrobing attachment but who work in very small batches and whose production is measured in hundreds of kilos per week, not per day.

Prima is the smallest continuous tempering machine on the market that accepts an enrobing attachment.

The continuous tempering cycle on the **Prima** is controlled by a custom-programmed dedicated CPU that monitors and adjusts heating and cooling automatically within a very narrow range based on the set melting and tempering points. The working bowl is heated by thermoelectric induction and the tempering pipe is cooled directly by the refrigerant gas, delivering fast response times, precise control, and reduced energy consumption.

3000W step-up transformer required for 120VAC operation (not included).

The auger in the **Prima's** tempering pipe automatically reverses for emptying and is removable for cleaning. A pedal-operated depositor with user-selectable time and repetitions (up to 9) for filling molds and other uses.

Key Standard Features

- Removable vibrating table
- Night cycle
- Removable/reversible tempering auger
- Pedal-operated electronic depositor with user-selectable time and repetitions

Optional Enrobing Attachment Features

- Overall length: 1.356 mm — Usable width 180mm
- Two pieces: 1) stainless steel entrance and working sections; 2) removable food-contact-safe take-off belt
- Equipped with adjustable bottomer, double-curtain veil, net beater, adjustable air blower, de-tailer

Key Specifications

- Capacity (bowl): 10kg (~22 pounds)
- Throughput: ~2.5x bowl capacity per hour, depending on the type of work being done
- Dimensions: 380(w) x 400(d) x 1200 (overall height); working plane @ 860mm
- Weight: ~90kg (~200 lbs)
- Installed power: 1300 watts @ 220V three-phase; w/enrober: 1400 watts

Pricing

CAT#. P103P	PRIMA — 220V 3-phase 60 Hz	€7,850
CAT#. P101P	Single phase 220V 60Hz	€8,500
CAT#. 2PENRO	Enrobing attachment (two-piece; separate removable exit section)	€5,100
Palletizing	Required for shipment	+ €80